

UNITED OIL COMPANY

Quality Industrial Lubricants Since 1906

1800 North Franklin Street

Pittsburgh, Pennsylvania 15233

PH: (412) 231-1269

FX: (412) 231-1384

UNITED NON STAINING BEARING OILS

United Oil Non-Staining Bearing Oils are high quality lubricants formulated to provide the necessary levels of friction reduction and wear protection required in bearing applications. The products resist water wash-off and have a long service life.

United Oil Bearing Oils are truly universal and can be used in applications that have historically required heavily compounded oils or straight oils. United Oil has developed these products using knowledge acquired from a long association with various metalworking operations.

United Oil Non-Staining Bearing Oils are recommended for all total loss applications where the special properties of these oils are needed. They can be used for bearings, gears, slides and way applications

TYPICAL INSPECTION CHARACTERISTICS

	<u>#2150</u>	<u>#2300</u>	<u>#2500</u>
VISCOSITY, SUS @100F.	2150	2300	2500
VI	90	90	90
SPECIFIC GRAVITY	0.8816	0.8816	0.8816
API GRAVITY @ 60F.	29	29	29
FLASH POINT, COC, F.	290	290	290
FIRE POINT, COC, F.	315	315	315
POUR POINT, F.	+15	+15	+15
ASTM D665 RUST TEST PARTS A & B	PASS	PASS	PASS