

UNITED OIL COMPANY

Quality Industrial Lubricants Since 1906

1800 North Franklin Street

Pittsburgh, Pennsylvania 15233

PH: (412) 231-1269

FX: (412) 231-1384

United Unidraw # 32A-25

(Rod drawing lubricant for all Aluminum and Aluminum Alloy)

Product Data Sheet

Product Description:

1. **Unidraw # 32A-25** was developed to provide a medium-low viscosity wire drawing product with superior lubrication for both EC and magnesium alloyed wire in high speed operations. The proprietary lubrication package incorporated into **Unidraw # 32A-25** allows for faster drawing speeds and lower die temperatures over an extended period of time while providing a bright and clean finish. **Unidraw # 32A-25** should be used neat, flooded directly into the tool/work piece interface. Suggested application is by high volume flooded or submerged.

Outstanding Qualities:

1. With adequate filtration and routine system maintenance, **Unidraw # 32A-25** offers exceptional sump life.
2. The viscosity characteristics of the oil permits easy filtering or centrifuging.

Technical Information:

| | |
|-----------------------|----------|
| Viscosity @100° F SUS | 950-1000 |
| Specific Heat @100° F | 0.48 |
| Flash Point, COC F | 560 |
| API Gravity @ 60° F | 27 |
| Saponification Value | 45-55 |